



Tourguide 2020-D

SR 2020-D



The SR 2020-D, multiply gifted! For each of your productions, the compact high-tech transmitter SR 2020-D will provide perfect audio in exactly the right way. It allows for conferences or presentations to be interpreted simultaneously in up to 8 languages. Other audio content can be selected from CD, DVD or your IT network.

Of course, you can connect microphones for announcements, and the system will even follow you on bus or boat tours. The transmitter is operated very easily and comfortably. Important parameters such as channel selection and line/mic input levels can be checked on the back-lit display.

DELIVERY INCLUDES

- SR 2020-D
- GA 2 rack mount
- NT 2-1 power supply unit
- Telescopic antenna
- Instruction manual

PRODUCT VARIANTS

SR 2020-D-US	Art. no. 500551
SR 2020-D	Art. no. 500550

ACCESSORIES

EK 2020-D-II	Receiver	Art. no. 504794
EK 2020-D-II-US	Receiver (US)	Art. no. 504795
HDE 2020-D-II	Stethoset receiver	Art. no. 504796
HDE 2020-D-II-US	Stethoset receiver (US)	Art. no. 504797

FEATURES

- Digital RF signal transmission
- 6 - 8 channels in the licence-free range
- 19" rack-mount kit included
- Easy configuration and usage
- Balanced XLR-3F-Input with switchable phantom-power (48 V)
- 6.3 mm jack-plug headphones connection for monitoring
- backlit LC Display

SPECIFICATIONS

Modulation	2 FSK (46K0F1D)
Frequency range	863 – 865 MHz
Frequency range (US)	926 – 928 MHz
Channels (tourguide mode)	6
Channels (conference mode)	8
Frequency response	100 - 7,000 Hz
Signal-to-noise-ratio	> 70 dBA
THD at 1 kHz	< 1 %
Input voltage range	160 mV - 2.5 V (Line), 2 mV - 125 mV (Mic)
Phantom Powering	48 V
Current consumption	max. 300 mA
Temperature range	0 – 50 °C
Range Indoor	up to 50 m
Range Outdoor	up to 100 m
Dimensions	212 x 145 x 38 mm
Weight	1100 g



Tourguide 2020-D

SR 2020-D

DIMENSIONS

